



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 577 358 A1**

(12)

**EUROPEAN PATENT APPLICATION**  
published in accordance with Art. 158(3) EPC

(43) Date of publication:

21.09.2005 Bulletin 2005/38

(51) Int Cl.7: **C09J 7/02**

(21) Application number: 03777190.4

(86) International application number:  
**PCT/JP2003/015458**

(22) Date of filing: 03.12.2003

(87) International publication number:  
**WO 2004/061032 (22.07.2004 Gazette 2004/30)**

(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
HU IE IT LI LU MC NL PT RO SE SI SK TR**

Designated Extension States:

**AL LT LV MK**

(72) Inventors:

- **KATO, Kichiro**  
Warabi-shi, Saitama 335-0005 (JP)
- **KATO, Kazuya**  
Warabi-shi, Saitama 335-0005 (JP)
- **TAKEMOTO, Takashi**  
Warabi-shi, Saitama 335-0005 (JP)

(30) Priority: 27.12.2002 JP 2002379279

28.08.2003 JP 2003304028

29.10.2003 WOPCT/JP03/13866

(74) Representative: Nicholls, Michael John

**J.A. KEMP & CO.,  
14, South Square,  
Gray's Inn  
London WC1R 5JJ (GB)**

(71) Applicant: **Lintec Corporation**  
Tokyo 173-0001 (JP)

**(54) ADHESIVE SHEET AND METHOD FOR MANUFACTURING SAME**

(57) The present invention relates to a pressure sensitive adhesive sheet 1 comprising a base material 11 and a pressure sensitive adhesive layer 12 wherein a plurality of through holes 2 passing through one face of the pressure sensitive adhesive sheet 1 to the other face are formed. The hole diameter of the through holes

2 is 0.1 to 300  $\mu\text{m}$  and the hole density is 30 to 50,000/100  $\text{cm}^2$ . It is preferable to form the through holes 2 using a laser beam machining. According the pressure sensitive adhesive sheet 1, an air trapping or a blister can be prevented or removed without disfiguring the pressure sensitive adhesive sheet and while securing a sufficient adhesive strength.

**Fig.1**

